



1711	MEDIDOR DE PROFUNDIDADE <i>Gauge</i>	1998	ESCARIADOR <i>Reamer</i>
1714	FIO LIÇO TROCATER Ø 2,0X150 mm <i>Smooth Wire</i>	1999	GUIA DE BROCA Ø 2,8 mm <i>Drill Guide</i>
1716	FIO 1,25 x 150 mm <i>Wire</i>	2081/01	AFASTADOR DE HOHMANN Ø 6,0 mm <i>Hohmann Retractor</i>
1717	MEDIDOR <i>Gauge</i>	2081/02	AFASTADOR DE HOHMANN Ø 8,0 mm <i>Hohmann Retractor</i>
1718	TORQUÍMETRO 1,5 Nm <i>Torque Wrench</i>	2083	AFASTADOR DE HOLMANN LARGA <i>Holmann Retractor Large End</i>
1718/01	TORQUÍMETRO 0,8Nm <i>Torque Wrench</i>	2105	PINÇA DE REDUÇÃO COM PONTO 140 mm <i>Reduction Forceps</i>
1719	CABO COM ENGATE RÁPIDO <i>Fast Connection Handle</i>	2106	PINÇA DE REDUÇÃO COM PONTAS 130mm <i>Reduction Forceps With Point</i>
1727	CHAVE SEXTAVADA 2,5 COM ENGATE RÁPIDO <i>Hexagonal Wrench with Fast Assembly</i>	2108/04	CHAVE SEXTAVADA 2,5 <i>Hex Head Screwdriver</i>
1800	GUIA DE BROCA Ø 2,0 / 2,5 mm <i>Drill Guide</i>	2254/01	AFASTADOR ADSON 140 mm <i>Adson Retractor</i>
1994	BROCA Ø 2,0 COM ENGATE RÁPIDO <i>Drill with Quick Coupling</i>	2621	FIO GUIA Ø1,2 X 150mm <i>Wire Guide</i>
1995	BROCA Ø 2,8 COM ENGATE RÁPIDO <i>Drill with Quick Coupling</i>	7500	CHAVE HEXAGONAL 2,0 mm <i>Hexagonal Wrench</i>
1996	FRESA MACHO Ø 3,5 mm <i>Reamer</i>	7502	GUIA DE BROCA Ø2,0 mm <i>Drill Guide</i>